

# **TR-188**

## **DSL Quality Suite**

**Issue: 1**  
**Issue Date: November 2010**

**Notice**

The Broadband Forum is a non-profit corporation organized to create guidelines for broadband network system development and deployment. This Broadband Forum Technical Report has been approved by members of the Forum. This Broadband Forum Technical Report is not binding on the Broadband Forum, any of its members, or any developer or service provider. This Broadband Forum Technical Report is subject to change, but only with approval of members of the Forum. This Technical Report is copyrighted by the Broadband Forum, and all rights are reserved. Portions of this Technical Report may be copyrighted by Broadband Forum members.

This Broadband Forum Technical Report is provided AS IS, WITH ALL FAULTS. ANY PERSON HOLDING A COPYRIGHT IN THIS BROADBAND FORUM TECHNICAL REPORT, OR ANY PORTION THEREOF, DISCLAIMS TO THE FULLEST EXTENT PERMITTED BY LAW ANY REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY:

- (A) OF ACCURACY, COMPLETENESS, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE;
- (B) THAT THE CONTENTS OF THIS BROADBAND FORUM TECHNICAL REPORT ARE SUITABLE FOR ANY PURPOSE, EVEN IF THAT PURPOSE IS KNOWN TO THE COPYRIGHT HOLDER;
- (C) THAT THE IMPLEMENTATION OF THE CONTENTS OF THE TECHNICAL REPORT WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

By using this Broadband Forum Technical Report, users acknowledge that implementation may require licenses to patents. The Broadband Forum encourages but does not require its members to identify such patents. For a list of declarations made by Broadband Forum member companies, please see <http://www.broadband-forum.org>. No assurance is given that licenses to patents necessary to implement this Technical Report will be available for license at all or on reasonable and non-discriminatory terms.

ANY PERSON HOLDING A COPYRIGHT IN THIS BROADBAND FORUM TECHNICAL REPORT, OR ANY PORTION THEREOF, DISCLAIMS TO THE FULLEST EXTENT PERMITTED BY LAW (A) ANY LIABILITY (INCLUDING DIRECT, INDIRECT, SPECIAL, OR CONSEQUENTIAL DAMAGES UNDER ANY LEGAL THEORY) ARISING FROM OR RELATED TO THE USE OF OR RELIANCE UPON THIS TECHNICAL REPORT; AND (B) ANY OBLIGATION TO UPDATE OR CORRECT THIS TECHNICAL REPORT.

Broadband Forum Technical Reports may be copied, downloaded, stored on a server or otherwise re-distributed in their entirety only, and may not be modified without the advance written permission of the Broadband Forum.

The text of this notice must be included in all copies of this Broadband Forum Technical Report.

**Issue History**

<b>Issue Number</b>	<b>Issue Date</b>	<b>Issue Editor</b>	<b>Changes</b>
1	November 2010	Mauro Tilocca, TI	Original

Comments or questions about this Broadband Forum Technical Report should be directed to [info@broadband-forum.org](mailto:info@broadband-forum.org).

<b>Editor</b>	Mauro Tilocca	Telecom Italia
<b>Operations&amp;Network Management WG Chair</b>	Peter Adams	ADTRAN
<b>Vice Chair</b>	Moti Morgenstern	ECI
<b>Chief Editor</b>	Michael Hanrahan	Huawei Technologies

**Table of Contents**

<b>1</b>	<b>PURPOSE AND SCOPE</b> .....	<b>6</b>
1.1	PURPOSE .....	6
1.1.1	<i>DSL line quality and stability</i> .....	6
1.2	SCOPE .....	8
<b>2</b>	<b>REFERENCES AND TERMINOLOGY</b> .....	<b>10</b>
2.1	CONVENTIONS .....	10
2.2	REFERENCES .....	10
2.3	ABBREVIATIONS .....	11
<b>3</b>	<b>TECHNICAL REPORT IMPACT</b> .....	<b>12</b>
3.1	ENERGY EFFICIENCY .....	12
3.2	IPV6 .....	12
3.3	SECURITY .....	12
<b>4</b>	<b>INTRODUCTION</b> .....	<b>13</b>
<b>5</b>	<b>DSL QUALITY SUITE COMPONENTS</b> .....	<b>15</b>
5.1	MANAGEMENT TECHNIQUES AND NOMENCLATURE COMPONENTS .....	15
5.1.1	<i>WT-197 “DQS: DSL Quality Management techniques and nomenclature”</i> .....	15
5.2	REQUIREMENTS COMPONENTS .....	15
5.2.1	<i>TR-198 “DQS: DQM systems functional architecture and requirements”</i> .....	15
5.2.2	<i>Gap analysis about DSL parameters collection needs</i> .....	16
5.2.3	<i>Testing framework for DQM-ready systems</i> .....	16
5.3	PROFILES CONFIGURATION GUIDELINES COMPONENTS .....	17
5.3.1	<i>TR-176 - ADSL2Plus Configuration Parameters for IPTV</i> .....	17
5.3.2	<i>TR-165 - Vector of Profiles (VoP)</i> .....	18
5.4	BEST PRACTICES COMPONENTS .....	18

## **Executive Summary**

This Technical Report aims to specify a framework for the management of Digital Subscriber Line (DSL) quality. The objective is to obtain a common reference to allow homogeneous definition of further documents devoted to specific management aspects. The building bricks for the effective management of all the quality and stability aspects of DSL lines are described, to be used both by Vendors and Service Providers. This framework document identifies a collection of Broadband Forum documents already existing or planned, ranging from nomenclature aspects to requirements and guidelines, and finishing with best practices for Service Providers.

The reader is advised that given the nature of this Technical Report, the Broadband Forum documents described as being the components of the DSL Quality Suite (DQS) can be in different status: publicly available, under development within the Broadband Forum, not started. The Broadband Forum is contribution driven, hence in the latter two cases there is no commitment those documents will eventually be published.

The reader is also advised this Technical Report is subject to updates to follow the evolution of the DQS framework. Hence the latest published version possibly does not fully reflect the current status of DQS specification work within the Broadband Forum.

This Technical Report is provided solely for information and does not contain any normative text. Normative text is confined to component documents of the DSL Quality Suite.

# 1 Purpose and Scope

## 1.1 Purpose

In the light of Broadband as tomorrow's universal means for communications and a multitude of other services, it is an unavoidable need to tackle the issue of DSL stability and quality by means of advanced and efficient techniques. As the penetration of broadband increases and the related service offers become more and more structured, such techniques represents a tool (or tools) of utmost importance. This is to guarantee overall service quality and performance to customers as well as consolidate broadband as a main service-enabling network platform for Service Providers.

This Technical Report contains the framework for a DSL Quality Suite (DQS) intended as a collection of Broadband Forum documents focused on the management of the quality and stability of DSL lines.

The reader is advised that the components of the DSL Quality Suite (DQS) can be in different status: publicly available, under development within the Broadband Forum, not started. The Broadband Forum is contribution driven, hence in the latter two cases there is no commitment those documents will eventually be published.

### 1.1.1 DSL line quality and stability

Generally speaking what counts in the provision of a communication or entertainment service is the quality perceived by the customer (aka Quality of Experience) and the fact that an appropriate degree of availability and usability are guaranteed.

For bundled offers, each service component has its own characteristics and requires a particular level of QoE, availability and usability so as that specific service be acceptable. In the following considerations, the concept of usability will be left out as it is often determined by the characteristics and GUI of the PC, terminal or appliance the customer uses to access the service(s).

Service availability and quality are highly influenced by the network it is transported through. When possible QoE and availability objectives are translated into QoS and connection availability targets at the different networking layers and apportioned among different network segments and nodes.

Following the above scheme, for broadband services delivered via a final access drop based on a DSL link it is a common practice to:

- define the concepts of DSL line stability and quality;
- identify one or more DSL parameters and elaborations of them as metrics to quantify DSL line stability and quality;

- identify targets for such metrics associated (e.g. derived empirically or “mathematically”) to higher layer quality metrics and ultimately to the quality and availability levels coherent with the service component(s) being transported over the DSL line.

Considering the characteristics of DSL transmission it is straightforward to associate the concept of:

- DSL stability with the time the line is synchronised, with parameters like Fullinit and Failed Full init, and with the associated alarm events (e.g. LOS, LOP, LPR).
- DSL quality with the error rate, with parameters like PM CRC counters and with the associated alarm and threshold crossing events.

This duality is very useful when collecting line data to monitor its status as experience teaches that trying to aggregate these aspects into one single all-purpose line metric can lead to a value that hardly links back to physical phenomena on the line.

The concepts of quality and stability can be regarded as two axes that concur to describe the status of the line. G.997.1 [1] naturally combines together these axis, as PM counters like ES, SES and UAS are triggered by root causes affecting either the quality axis (i.e. CRC violations) or the stability one (line drops with the associated alarm indications).

This is inherently tied to the concept of DSL availability, also embedded in the UAS counters themselves:

- DSL availability requires that the link is sufficiently stable, e.g. number of resynchronisations per day acceptable, and has sufficient quality, e.g. average and instantaneous BER acceptable, with regard to carried service components.

This attribute can be very useful, on the other hand, when it comes to diagnose a line and decide on corrective actions it can be beneficial to simpler to refer to qualitative categories that bring together the stability and quality status. As a simple matter of example one can define a line as:

- Bad: DSL link is mostly unavailable or transmission suffers from high degradation
- Poor: DSL link is sometimes unavailable or suffers from little degradation (associated to noticeable impact to customer QoE)
- Good: DSL link is available and (almost) error free (with service experience as good as defined in TR-126)
- Unknown: not enough data to determine actual status

The assessment of DSL line availability is key as this is a necessary (though not sufficient) condition for the service to be available. Then on top of DSL availability, other parameters (e.g. current and attainable bitrate, delay, time statistic of the noise margin, etc.) can be considered to assess the line’s attitude to carry current service components, to be resilient to increases to DSL penetration in the binder and to support service changes/upgrades.

As said above, the stability and quality of the line can be quantified by the elaboration of certain DSL parameters but clearly they need to be tightly linked to information related to carried services, to operators specific practices, customer selfcare input and other relevant data.

Under the context above the concept of **DSL Quality Management (DQM)** is introduced as the abstract **capability of pro-active and efficient control of the quality and stability** of broadband lines.

By definition, the scope of DQM fully resides within the DSL domain but this is only a working hypothesis that allows to well identify the boundaries of the DSL Quality Suite as a structured Broadband Forum project.

As clearly stated above the ultimate objective is service and all its attributes that concur to form the customer perception which in turn answers to the inherent *“pay-for-value”* commitment that is behind any service offer.

Under this perspective DSL quality and stability, as the key objective of DQM, have to be always regarded as a contribution to the overall service perception and have to be treated, in Network Operation and Maintenance processes, in strict coordination with all other influencing parameters and metrics.

## 1.2 Scope

The aim of the DQS is to identify the building blocks (reference features and tools, equipment and system requirements, network strategies and practices) to be used by vendors and Service Providers to develop solutions that enable pro-active and efficient maintenance of broadband lines and services. Furthermore the explicit definition of requirements for such solutions can be used by operators as a reference for tenders and system validation. Finally some guidelines for Service Providers, coming from suggested profiles and best practices are conceived as a useful part to complete this Suite.

The DQS scope mainly takes into account ADSL, ADSL2, ADSL2plus and VDSL2 technologies and focuses on DSL parameters and metrics to guarantee and ameliorate the quality and availability of the “physical layer service” over a copper pair.

Nevertheless, as discussed in the previous section, DQM techniques have to be considered part of more complex processes encompassing different segments of the whole network connection and have to be applied in coordination with techniques associated to higher layers.

Finally DQM techniques need to be driven by the service components actually being delivered over a specific DSL line. As far as the types of services, not only IPTV is taken into consideration but all the components of today’s triple-play offers (e.g. HSI, VoIP, IPTV) are dealt with either alone or bundled onto the DSL line.

The list of documents below describes the components that contribute to the DSL Quality Suite as a structured project. This list can change in time depending on the actual course of the works



within the involved Working Group(s) and each version of this framework document identifies the status of the DQS components as a published TR or an ongoing/planned Broadband Forum WT/PD.

For completeness this Technical Report can also point to documents from other Standards Developing Organizations (SDOs).

## 2 References and Terminology

### 2.1 Conventions

This Technical Report is solely informative and therefore does not contain any normative text. There are no conventions relating to requirements. Normative text is confined to component documents of the DSL Quality.

### 2.2 References

The following references are of relevance to this Technical Report. At the time of publication, the editions indicated were valid. All references are subject to revision; users of this Technical Report are therefore encouraged to investigate the possibility of applying the most recent edition of the references listed below.

A list of currently valid Broadband Forum Technical Reports is published at [www.broadband-forum.org](http://www.broadband-forum.org).

Document	Title	Source	Year
[1] G.997.1	<i>Physical layer management for digital subscriber line (DSL) transceivers</i>	ITU-T	2009
[2] G.996.2	<i>Line Testing for Digital Subscriber lines (DSL)</i>	ITU-T	2009
[3] TR-129	<i>Protocol-Independent Management Model for Next Generation DSL Technologies</i>	Broadband Forum	2006
[4] WT-160	<i>IPTV Performance Monitoring and Diagnostics</i>	Broadband Forum	
[5] TR-100	<i>ADSL2/ADSL2plus Performance Test Plan</i>	Broadband Forum	2007
[6] TR-176	<i>ADSL2Plus Configuration Parameters for IPTV</i>	Broadband Forum	2008
[7] TR-105	<i>ADSL2/ADSL2plus Functionality Test Plan</i>	Broadband Forum	2008
[8] TR-114	<i>VDSL2 Functionality Test Plan</i>	Broadband Forum	2009
[9] TR-115	<i>VDSL2 Performance Test Plan</i>	Broadband Forum	2009
[10] TR-138	<i>Accuracy Tests for Test Parameters</i>	Broadband Forum	2009
[11] TR-165	<i>Vector of Profiles</i>	Broadband Forum	2009
[12] TR-198	<i>DQS: DQM systems functional architecture and requirements</i>	Broadband Forum	2010
[13] TR-252	<i>xDSL Protocol-Independent Management Model</i>	Broadband Forum	2010

[14] WT-197      *DQS: DSL Quality Management techniques and nomenclature*      Broadband Forum

### 2.3 Abbreviations

This Technical Report uses the following abbreviations:

<b>BBF</b>	Broadband Forum
<b>DLM</b>	Dynamic Line Management
<b>DQM</b>	DSL Quality Management
<b>DQS</b>	DSL Quality Suite
<b>DSL</b>	Digital Subscriber Line
<b>DSM</b>	Dynamic Spectrum Management
<b>DSLAM</b>	Digital Subscriber Line Access Multiplexer
<b>EM</b>	Element Manager
<b>HSI</b>	High-Speed Internet
<b>IP</b>	Internet Protocol
<b>IPTV</b>	IP Television
<b>MD</b>	Marketing Draft
<b>MR</b>	Marketing Report
<b>NMS</b>	Network Management System
<b>ONU</b>	Optical Network Unit
<b>PD</b>	Proposed Draft
<b>SDO</b>	Standards Development Organization
<b>TR</b>	Technical Report
<b>WG</b>	Working Group
<b>WT</b>	Working Text
<b>VoIP</b>	Voice over IP

### **3 Technical Report Impact**

#### **3.1 Energy Efficiency**

TR-188 has impact on Energy Efficiency in that some of the DSL Quality Suite components have. More details are given in specific DQS components.

#### **3.2 IPv6**

TR-188 has no impact on IPv6.

#### **3.3 Security**

TR-188 has no impact on Security.

## 4 Introduction

Historically DSL standardisation has been quite focused on transceivers requirements and their ability to deliver increasing bitrates along with link features often tailored to that purpose. This is a natural consequence of operators and vendors aim of deploying broadband services maximising coverage and speed.

After the take up and growth phase, the issue of DSL quality and stability has become more and more important with:

- the increase of copper based broadband penetration;
- the introduction multi-play service offers with stricter QoE requirements;
- the need to consistently and reliably sustain the revenue stream generated by the copper infrastructure and services and also to allow a smoother transition paths towards fiber based deployments.

The DQS is a structured framework of standards to guide the international community in the development and exploitation of network equipment and systems specifically designed to apply sophisticated and scalable DQM techniques.

This section describes the DQS structure in terms of its components and their mutual relationship. A component is a published TR or a Working Text/Proposed Draft that is being or can be developed by the relevant Technical WG(s) of the Broadband Forum.

In the following heading structure and sections text, documents labelled as:

- TR or MR, have already been published by the Broadband Forum
- WT, PD or MD, have already been initiated and are under development by the Broadband Forum and, as such, are only available to Broadband Forum members.

When no tag is associated to a document or area of work it means that no drafting has been started though that area is recognised as relevant within the DQS framework.

Each component, though with different degrees of importance, contributes to the overall DQS framework as part of a specific category.

Following a logical order the identified DQS categories are as follows:

- the **management techniques and nomenclature** category relates to definitions which clarify the use of terminology and acronyms related to DQM and the description of the techniques and parameters to enhance DSL quality and stability.
- the **requirements** category addresses the features and capabilities needed on the equipment and/or management systems to effectively implement the management techniques for DSL quality and stability.

- the **configuration** category deals with the line profiles suggested for specific services or specific DSL technologies when addressing the trade-off between quality/stability and other link characteristics such as bitrate, delay, etc.
- the **best practices** category depicts currently adopted Network Operation practices.

The above list does not preclude the addition of further categories as deemed necessary.

The DQS structure contained in this Technical Report represents a main guideline, nevertheless it is not intended as a mandatory document, instead it serves as a tool to describe and manage the DQS from a high level perspective and its versions will be adapted to follow the evolution of its components.

## 5 DSL Quality Suite components

This section describes the components of the DSL Quality Suite taking into account the structure and categories depicted in chapter 4. This is done bearing in mind that the DQS aims to provide a structured standardization framework to address DQM issues both in the domain of marketplace solutions and for network operation purposes. More specifically for each of the DQS categories and each of its identified components, its relevance in the DQM problem area are explained.

### 5.1 Management techniques and nomenclature components

These documents aim to provide the international community with a unified nomenclature about the techniques and strategies available to address DSL stability and quality issues. They define a common language to refer to parameters, functionalities and typical network practices in the above problem space.

Such an ‘alphabet’ is a fundamental prerequisite for the specification of requirements for systems enabling effective Network Operation strategies.

Furthermore the components under this section are developed in a way that their content is easily understandable by less expert readers.

#### 5.1.1 WT-197 “DQS: DSL Quality Management techniques and nomenclature”

A number of different schemes and acronyms can be found in the literature (e.g. DSM, DLM, etc.) for defining the techniques and strategies for monitoring and assuring DSL stability and quality. Sometimes these names and conceptual approaches are also used by commercial products or within the operational work-flows of access networks.

The purpose of WT-197 [14] is to define a common nomenclature and a unified framework to describe functionalities, tools, techniques and strategies that are already available or under study for the support of DSL Quality Management. Such unified taxonomy of DQM “enablers” represents a very useful toolkit for DQM-enabled solutions design and for network provisioning and assurance strategies.

In building such a taxonomy the focus is put on the issues and problems to be solved rather than the implemented algorithms. Furthermore the energy efficiency impact of each technique is described.

### 5.2 Requirements components

This section refers to documents that specify requirements for systems to be ready for supporting DSL Quality Management. Historically few specific DQM architectural, functional/performance and interface requirements have been standardised and adopted by the industry. This has resulted in very diversified support, with a lack of features and capabilities needed to deploy sophisticated and scalable DQM techniques.

#### 5.2.1 TR-198 “DQS: DQM systems functional architecture and requirements”

A management network architecture enabling DSL Quality Management is composed of different systems that, broadly speaking, need to:

- collect relevant information related to DSL line behavior,
- analyze line parameters,
- modify the DSL profile, on a line or bundle basis, to improve line stability and/or performances.

The systems involved in the DQM architecture are both broadband equipment (DSLAMs, ONUs, etc) and management systems (e.g. EM or NMS). Current standards specify features and requirements for DSL transceivers, equipment and related management systems but there does not exist a self-consistent specification which defines the capabilities supported by the overall network architecture (management systems and network of equipment) to enable DQM within Network Operation practices. The functional and system requirements specified have to be seen as a whole set applicable to the abstract DQM-entity without any mandatory specification(s) about their apportionment onto each of the involved network resources.

The macro-categories of requirements encompassed by TR-198 [12] are:

- line status, test and performance parameters (at DSL physical layer),
- DSL functionalities,
- DSL configuration,
- responsiveness and general accessibility of line parameters,
- flexible storage and scheduling features for line parameters monitoring/collection.

### **5.2.2 Gap analysis about DSL parameters collection needs**

A system implementing DSL Quality Management relies on the capability to assess the DSL line behavior, identify its noise environment and impairments that could limit maximum achievable performances.

G.997.1 [1] already provides a comprehensive set of DSL parameters. Other initiatives among different standardization bodies are now in place in order to enhance the available diagnostic features on DSL lines (e.g. ITU-T G.996.2[2], WT-160 [4], the ATIS DSM TR and other work in the regional bodies, etc)

The purpose of this component is to:

- identify relevant parameters that allow an optimal diagnosis of DSL lines,
- identify gaps in available performance monitoring parameters and features currently specified in the standards and propose new capabilities,
- guide and stimulate the standardization of those parameters that are essential, or desirable, for DSL Quality Management but not yet included in DSL standards.

The Broadband Forum efforts with respect to performing this gap analysis as part of the DQS are for further study.

### **5.2.3 Testing framework for DQM-ready systems**

This component is conceived as a collection of pointers to specific test procedures or dedicated test plans focused on the verification of DQM related features and capabilities.



One set of this collection contains the test configurations and procedures, defined in some Broadband Forum Test Plans, dealing with the validation of the functionality and performance of equipment directly related to DSL quality and stability. As an example pointers to tests under impulsive noise and other types of line threats are appropriate for inclusion in such components. The following Broadband Forum Test Plans specify Test Cases for the verification of functionalities and performances of DSLAMs and CPEs which are relevant for a DQM-ready system:

- TR-105 - ADSL2/ADSL2plus Functionality Test Plan [7]
- TR-100 - ADSL2/ADSL2plus Performance Test Plan [5]
- TR-114 - VDSL2 Functionality Test Plan [8]
- TR-115 - VDSL2 Performance Test Plan [9]
- TR-138 - Accuracy Tests for Test Parameters [10]

Tests for the verification of system level features that enable DQM strategies are also part of this component.

More specifically WT-260 “DCF functional and performance Test Plan” specifies functional and performance tests for the Data Collection Function defined in TR-198 and is aimed to help the verification and maturing of DCF implementations.

The Broadband Forum efforts with respect to defining a Testing framework for DQM-ready systems as part of the DQS are currently under study.

### **5.3 Profiles configuration guidelines components**

These components contain the principles, methods and recommended values for DSL configuration profiles.

It is known as not viable to adopt a “one-fits-all” approach in the physical layer configuration. Hence it is mostly useful to define guidelines for choosing parameters values for different DSL flavours (ADSL2plus, VDSL2, etc), type of offered service (HSI, VoIP, IPTV or a mix of them) or for specific copper pair conditions (length and observed types of impairments).

The Broadband Forum efforts with respect to developing profiles configuration guidelines in support to DQM strategies as part of the DQS are for further study.

#### **5.3.1 TR-176 - ADSL2Plus Configuration Parameters for IPTV**

As stated in TR-176 [6], this Broadband Forum Technical Report “... contains generic ADSL2plus configuration parameter settings for use in the deployment of IPTV over ADSL2plus. Included are ranges of deployed parameter values derived from the experiences of service providers and vendors who have already tested, trialed and/or deployed IPTV over ADSL2plus and hence represent current industry practice. In addition, specific recommendations are made for a baseline set of parameters supporting IPTV. ...”

### 5.3.2 TR-165 - Vector of Profiles (VoP)

As stated in TR-165 [11], “this Working Text addresses the need for greater flexibility in setting DSL profiles by defining a vector of profiles. The DSL configuration parameters are divided into independent, but technically related, sets of parameters. Each parameter set defines a profile. The profiles are referenced from a vector of indices, each index identifying a unique profile. This allows a large number of profiles to be used without having to store huge quantities of profile data. The Vector of Profiles is a key enabler to DSL Quality Management. It is also expected to help Network Operators in the implementation of efficient and cost-effective Network Operation processes such as Network Creation, Service Delivery, Service Assurance and Troubleshooting.”

Evolutions of the Vector of Profiles specifications are being developed under Broadband Forum WT-252 [13], which encompasses DSL configuration based on a VoP, currently specified in TR-165, and other object model aspects (e.g. Performance Monitoring, alarms) currently specified in TR-129 [3]. The first issue of WT-252 is published as TR-252.

### 5.4 Best practices components

These components describe best practices in the use of DQM as a stability tool to optimize single-play and multi-play services over copper lines.

Use cases, experiences and suggestions are presented in these components.

The Broadband Forum efforts with respect to describing DQM best practices as part of the DQS are for further study.

End of Broadband Forum Technical Report TR-188